





MALE-MALE ADAPTER SLIDE-SLIDE TYPE
BOARD TO BOARD 11.7MM

R223.703.020

Series : **MMBX**



All dimensions are in mm.



COMPONENTS	MATERIALS	PLATING (μm)
BODY	BRONZE	NPGR
CENTER CONTACT	CUPRO BERYLLIUM	NPGR
OUTER CONTACT	-	-
INSULATOR	PTFE	-
GASKET	-	-
OTHERS PARTS	-	-
-	-	-
-	-	-

Issue : 0827 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



MALE-MALE ADAPTER SLIDE-SLIDE TYPE
BOARD TO BOARD 11.7MM

R223.703.020

Series : **MMBX**

PACKAGING

SPECIFICATION

Standard	Unit	Other
100	'W' option	Contact us

ELECTRICAL CHARACTERISTICS

ENVIRONMENTAL

Impedance	50	Ω
Frequency	0-12.4	GHz
VSWR	1.15* + 0.0000	x F(GHz) Maxi
Insertion loss	0.18	\sqrt{F} (GHz) dB Maxi
RF leakage	- (100**)	- F(GHz) dB Maxi
Voltage rating	330	Veff Maxi
Dielectric withstanding voltage	500	Veff mini
Insulation resistance	1000	M Ω mini

Operating temperature	-55/+155	$^{\circ}$ C
Hermetic seal	NA	Atm.cm3/s
Panel leakage	NA	

OTHER CHARACTERISTICS

Assembly instruction **NA**

Others :

* to 6 GHz

** Interface MMBX only up to 2.5 GHz

PCB to PCB -50dB up to 2.5Ghz

MECHANICAL CHARACTERISTICS

Center contact retention		
Axial force – Mating end	10	N mini
Axial force – Opposite end	10	N mini
Torque	NA	N.cm mini
Recommended torque		
Mating	NA	N.cm
Panel nut	NA	N.cm
Mating life	100	Cycles mini
Weight	0.4000	g

Issue : 0827 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

